



An Oshkosh Corporation Company

SPECIFICATIONS FOR MODEL PJC-600 CARTRIDGE DUST COLLECTION

MODEL CON-E-CO-PJC-600

NUMBER OF CARTRIDGES	8
NOMINAL CARTRIDGE DIAMETER	8"
NOMINAL CARTRIDGE LENGTH	78"
TOTAL FILTRATION AREA	608 SQ. FT.
MIN. DESIGN EFFICIENCY OF DUST COLLECTOR	99.9%
AIR TO CLOTH RATIO	5.0 TO 1.0
RATED AIR FLOW	3040 CFM
DISCHARGE AREA	1.29 SQ. FT.
DISCHARGE VELOCITY	39 FT. / SEC.
DIRECTION OF AIR DISCHARGE	DOWNWARD
OUTLET MOISTURE CONTENT	IDEALLY ZERO
NORMAL OPERATING TEMP & PRESSURE	AMBIENT
CLEANING MECHANISM	PULSE JET
FREQUENCY OF CLEANING	VARIABLE

CARTRIDGE SPECIFICATIONS

CARTRIDGE DIAMETER	7 7/8" O.D.
CARTRIDGE LENGTH	78 3/4"
CONSTRUCTION	PLEATED
FIBER	SPUN BONDER POLYESTER
WEIGHT	8 OZ / SQ. YD.
PERMEABILITY (.5" WATER)	24 CFM/SQ FT

DISCHARGE INTO BAGS

CEMENT SILO

LB / HR
GR / FT³

INTO BAGS

.177 LB/YD³ * ___ YD³/HR
.038 GR HR/LB FT³ * ___ LB/HR

FLYASH SILO

LB / HR
GR / FT³

INTO BAGS

.115 LB/YD³ * ___ YD³/HR
.038 GR HR/LB FT³ * ___ LB/HR

OUT OF BAGS

FOR ALL OUT OF BAGS VALUES, MULTIPLY THE INTO BAGS VALUES BY .001



SOLID PRODUCTS. SOLID PERFORMANCE.

237 N. 13TH ST - PO Box 430 - Blair, NE 68008

Phone: 800-656-2651 Fax: 402-426-4181 Service/Parts Fax: (402)-533-9292

E-MAIL: parts@con-e-co.com WEBSITE: www.con-e-co.com